AMENDMENTS TO THE CLAIMS:

This listing of claims will replace all prior versions, and listings, of claims in the application:

LISTING OF CLAIMS:

Claims 1 to 13. (Canceled).

- 14. (New) A ball socket for receiving a ball, comprising: at least one elastically deformable region.
- 15. (New) The ball socket according to claim 14, wherein the elastically deformable region is formed of an elastically deformable material.
- 16. (New) The ball socket according to claim 14, wherein the elastically deformable region includes an elastically deformable geometry.
- 17. (New) The ball socket according to claim 14, wherein the ball socket is adapted to cover a ball portion of the ball, the ball portion delimited by at least one circle.
- 18. (New) The ball socket according to claim 14, wherein the ball socket is adapted to cover a ball portion of the ball, the ball portion delimited by two circles arranged parallel to one another, the ball socket arranged as a ball layer
- 19. (New) The ball socket according to claim 14, wherein the ball socket includes at least one gap.
- 20. (New) The ball socket according to claim 19, wherein the gap is oriented perpendicular to at least one circle that delimits a ball portion of the ball that is covered by the ball socket.
- 21. (New) The ball socket according to claim 19, wherein the elastically deformable region is arranged as an elongate portion arranged diagonally with respect to the gap.

NY01 1144420 4

- 22. (New) The ball socket according to claim 19, wherein the at least one gap includes two gaps arranged diagonally with respect to one another along a circumference of the ball.
- 23. (New) The ball socket according to claim 22, wherein the elastically deformable region is arranged in one of the two gaps.
- 24. (New) The ball socket according to claim 17, wherein the elastically deformable region is arranged between a first portion of the circle and a second portion of the circle.
- 25. (New) The ball socket according to claim 18, wherein the elastically deformable region is arranged between a first portion of the circles and a second portion of the circles.
- 26. (New) The ball socket according to claim 14, wherein the elastically deformable region includes a thin-walled region.

27. (New) A system, comprising:

a rotatably mounted connection arrangement adapted to connect a first part to a second part in a vehicle, the first part including ball as a connection element, the second part including a ball socket as a connection element and adapted to receive the ball, the second part including at least one elastically deformable region.

NY01 1144420 5